

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

140164 Primaprint SP VR Developer Replenisher T/M 2x40L

Revision 1
Revision date 2017-01-23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 140164 Primaprint SP VR Developer Replenisher T/M 2x40L

1.3. Details of the supplier of the safety data sheet


Company	Champion Photochemistry Sdn Bhd
Address	Lot 28-B Mukim Batu Industrial Area 6 1/2 Miles Jalan Kepong 52000 Kuala Lumpur MALAYSIA
Web	www.championphotochemistry.com
Telephone	+603-6257 2600
Fax	+603-6257 2622

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	C; R35 Xn; R22-40 Xi; R43 N; R51/53 Symbols: Xn: Harmful.
Main hazards	Harmful if swallowed. Causes severe burns. Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
2.1.2. Classification - EC 1272/2008	Acute Tox. 4: H302; Skin Corr. 1A: H314; Skin Sens. 1: H317; STOT SE 3: H335; Aquatic Chronic 2: H411;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Acute Tox. 4: H302 - Harmful if swallowed. Skin Corr. 1A: H314 - Causes severe skin burns and eye damage. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

140164 Primaprint SP VR Developer Replenisher T/M 2x40L

Revision 1

Revision date 2017-01-23

2.2. Label elements

Precautionary Statement: Response	<p>P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ /if you feel unwell.</p> <p>P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.</p> <p>P302+P352 - IF ON SKIN: Wash with plenty of water/ .</p> <p>P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 -Immediately call a POISON CENTER/doctor/ .</p> <p>P312 - Call a POISON CENTER/doctor/ /if you feel unwell.</p> <p>P321 - Specific treatment (see on this label).</p> <p>P330 - Rinse mouth.</p> <p>P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P363 - Wash contaminated clothing before reuse.</p> <p>P391 - Collect spillage.</p>
Precautionary Statement: Storage	<p>P403+P233 - Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 - Store locked up.</p>
Precautionary Statement: Disposal	<p>P501 - Dispose of contents/container to hazardous or special waste collection point.</p>

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Potassium Carbonate		584-08-7	209-529-3		10 - 20%	Xi; R36/37/38	
Diethylene glycol	603-140-00-6	111-46-6	203-872-2		20 - 30%	Xn; R22	
DI Water		7732-18-5			10 - 20%		
4-(N-Ethyl-N-2-methanesulphonylaminoethyl)-2-methylphenylenediamine sesquisulphate monohydrate	612-134-00-2	25646-71-3	247-161-5		1 - 10%	Xn; R22 R43 N; R50/53	
Diethylhydroxylamine 85% w/w		3710-84-7	223-055-4		1 - 10%	Xn; R20/21 Xi; R36/37/38 R10-53	
Pentasodium DTPA Solution 42%		140-01-2	205-391-3		1 - 10%	C; R35 Xn; R22-40	
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5		1 - 5%	C; R35	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Potassium Carbonate		584-08-7	209-529-3		10 - 20%	Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335;	
Diethylene glycol	603-140-00-6	111-46-6	203-872-2		20 - 30%	Acute Tox. 4: H302;	
DI Water		7732-18-5			10 - 20%		
4-(N-Ethyl-N-2-methanesulphonylaminoethyl)-2-methylphenylenediamine sesquisulphate monohydrate	612-134-00-2	25646-71-3	247-161-5		1 - 10%	Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;	
Diethylhydroxylamine 85% w/w		3710-84-7	223-055-4		1 - 10%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Acute Tox. 4: H312; Acute Tox. 4: H332;	
Pentasodium DTPA Solution 42%		140-01-2	205-391-3		1 - 10%	Eye Dam. 1: H318; Acute Tox. 4: H332;	
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5		1 - 3%	Skin Corr. 1A: H314;	

SECTION 4: First aid measures

4.1. Description of first aid measures

140164 Primaprint SP VR Developer Replenisher T/M 2x40L

Revision 1
Revision date 2017-01-23

4.1. Description of first aid measures

Inhalation	Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Causes burns. Causes severe inflammation and may damage the cornea. Seek medical attention. Irritating to eyes.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion causes burns to the respiratory tract. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Not applicable. This product is not flammable.
--	--

5.2. Special hazards arising from the substance or mixture

	Corrosive. Burning produces irritating, toxic and obnoxious fumes.
--	--

5.3. Advice for firefighters

	Protective equipment. Wear suitable respiratory equipment when necessary. In case of fire and/or explosion do not breathe fumes.
--	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters


8.1.1. Exposure Limit Values

Diethylene glycol	WEL 8-hr limit ppm: 23	WEL 8-hr limit mg/m3: 101
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
	Sodium hydroxide	WEL 8-hr limit ppm: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: 2
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

140164 Primaprint SP VR Developer Replenisher T/M 2x40L

Revision 1
Revision date 2017-01-23

8.2. Exposure controls

	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear: Self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Orange
Odour	Slight
Upper Explosive Limit	Not relevant
Lower Explosive Limit	Not relevant
Vapour pressure	Not relevant
Vapour density	Not relevant
Partition coefficient (n-octanol/water)	Not relevant
Autoignition temperature	Not relevant
Decomposition temperature	No data available
Viscosity	Not determined
Odour threshold	Not relevant
pH	12.5
Melting point	Not relevant
Freezing Point	No data available
Initial boiling point	Not determined
Flash point	Not relevant
Evaporation rate	Not determined
Flammability (solid, gas)	Not relevant
Solubility	Soluble in water

9.2. Other information

Specific gravity	1.2 g/cm ³
------------------	-----------------------

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation	May cause irritation to skin. Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Repeated or prolonged exposure	May cause allergic reactions in susceptible people. May cause severe irritation to eyes and skin.

11.1.4. Toxicological Information

140164 Primaprint SP VR Developer Replenisher T/M 2x40L

Revision 1
Revision date 2017-01-23

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--	---

12.3. Bioaccumulative potential

Partition coefficient

	Pentasodium DTPA Solution <0 42%
--	-------------------------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

Disposal methods

	Do not empty into drains; dispose of this material and its container in a safe way. Do NOT mix with any other product. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
--	---

SECTION 14: Transport information

14.1. UN number

	The product is not classified as dangerous for carriage.
--	--

14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.
--	--

14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.
--	--

14.4. Packing group

	The product is not classified as dangerous for carriage.
--	--

14.5. Environmental hazards

	The product is not classified as dangerous for carriage.
--	--

14.6. Special precautions for user

	The product is not classified as dangerous for carriage.
--	--

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

Further information

	Not regulated.
--	----------------

SECTION 16: Other information

Other information

Revision

	This document differs from the previous version in the following areas: 9 - 9.1. Information on basic physical and chemical properties (Initial boiling point). 9 - 9.1. Information on basic physical and chemical properties (Melting point). 9 - 9.1. Information on basic physical and chemical properties (Flash point). 9 - 9.1. Information on basic physical and chemical properties (Flammability (solid, gas)). 9 - 9.1. Information on basic physical and chemical properties (Autoignition temperature). 9 - 9.1. Information on basic physical and chemical properties (Vapour pressure).
--	--

140164 Primaprint SP VR Developer Replenisher T/M 2x40L

Revision 1

Revision date 2017-01-23

Other information

	<p>9 - 9.1. Information on basic physical and chemical properties (Viscosity).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Vapour density).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Evaporation rate).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Upper Explosive Limit).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Lower Explosive Limit).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Decomposition temperature).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Partition coefficient (n-octanol/water)).</p> <p>9 - 9.1. Information on basic physical and chemical properties (Odour threshold).</p> <p>12 - 12.1. Toxicity.</p>
Text of risk phrases in Section 3	<p>R10 - Flammable</p> <p>R20/21 - Harmful by inhalation and in contact with skin.</p> <p>R22 - Harmful if swallowed.</p> <p>R35 - Causes severe burns.</p> <p>R36/37/38 - Irritating to eyes, respiratory system and skin.</p> <p>R40 - Limited evidence of a carcinogenic effect.</p> <p>R43 - May cause sensitisation by skin contact.</p> <p>R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R53 - May cause long-term adverse effects in the aquatic environment.</p>
Text of Hazard Statements in Section 3	<p>Skin Irrit. 2: H315 - Causes skin irritation.</p> <p>Eye Irrit. 2: H319 - Causes serious eye irritation.</p> <p>STOT SE 3: H335 - May cause respiratory irritation.</p> <p>Acute Tox. 4: H302 - Harmful if swallowed.</p> <p>Skin Sens. 1: H317 - May cause an allergic skin reaction.</p> <p>Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.</p> <p>Flam. Liq. 3: H226 - Flammable liquid and vapour.</p> <p>Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.</p> <p>Acute Tox. 4: H312 - Harmful in contact with skin.</p> <p>Acute Tox. 4: H332 - Harmful if inhaled.</p> <p>Eye Dam. 1: H318 - Causes serious eye damage.</p> <p>Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.</p>

Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---