

## SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

### 140169 Primaprint RA38 Developer Replenisher Part A T/M 2x50L

Revision 3

Revision date 2018-07-25

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

<b>Product name</b>	140169 Primaprint RA38 Developer Replenisher Part A T/M 2x50L
---------------------	---

##### 1.3. Details of the supplier of the safety data sheet


<b>Company</b>	Champion Photochemistry Sdn Bhd
<b>Address</b>	Lot 28-B Mukim Batu Industrial Area 6 1/2 Miles Jalan Kepong 52000 Kuala Lumpur MALAYSIA
<b>Web</b>	www.championphotochemistry.com
<b>Telephone</b>	+603-6257 2600
<b>Fax</b>	+603-6257 2622

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

<b>2.1.2. Classification - EC 1272/2008</b>	Asp. Tox. 1: H304;
---	--------------------

##### 2.2. Label elements

<b>Hazard pictograms</b>	
<b>Signal Word</b>	Danger
<b>Hazard Statement</b>	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
<b>Precautionary Statement: Response</b>	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P331 - Do NOT induce vomiting.
<b>Precautionary Statement: Storage</b>	P405 - Store locked up.
<b>Precautionary Statement: Disposal</b>	P501 - Dispose of contents/container to hazardous or special waste collection point.

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
DI Water		7732-18-5			50 - 60%		
Diethylene glycol	603-140-00-6	111-46-6	203-872-2		5 - 10%	Xn; R22	
Diethylhydroxylamine 85% w/w		3710-84-7	223-055-4		5 - 10%	Xn; R20/21 Xi; R36/37/38 R10-53	

## 140169 Primaprint RA38 Developer Replenisher Part A T/M 2x50L

Revision 3

Revision date 2018-07-25

## 3.2. Mixtures

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
DI Water		7732-18-5			50 - 60%		
Diethylene glycol	603-140-00-6	111-46-6	203-872-2		5 - 10%	Acute Tox. 4: H302;	
Diethylhydroxylamine 85% w/w		3710-84-7	223-055-4		5 - 10%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Acute Tox. 4: H312; Acute Tox. 4: H332;	

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

<b>Inhalation</b>	Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
<b>Eye contact</b>	Causes burns. Causes severe inflammation and may damage the cornea. Seek medical attention. Irritating to eyes.
<b>Skin contact</b>	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
<b>Ingestion</b>	Ingestion causes burns to the respiratory tract. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

	Not applicable. This product is not flammable.
--	--

## 5.2. Special hazards arising from the substance or mixture

	Corrosive. Burning produces irritating, toxic and obnoxious fumes.
--	--

## 5.3. Advice for firefighters

	Protective equipment. Wear suitable respiratory equipment when necessary. In case of fire and/or explosion do not breathe fumes.
--	--

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
--	---

## 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

## 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	--

## 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## 8.1.1. Exposure Limit Values

## 140169 Primaprint RA38 Developer Replenisher Part A T/M 2x50L


Revision 3

Revision date 2018-07-25

## 8.1.1. Exposure Limit Values

Diethylene glycol	WEL 8-hr limit ppm: 23	WEL 8-hr limit mg/m3: 101
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total inhalable dust: -	WEL 15 min limit mg/m3 total inhalable dust: -
	WEL 8-hr limit mg/m3 total respirable dust: -	WEL 15 min limit mg/m3 total respirable dust: -

## 8.2. Exposure controls

	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear: Self-contained breathing apparatus.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Yellow
Odour	Pleasant
Odour threshold	Not relevant
pH	11
Melting point	Not relevant
Initial boiling point	Not determined
Flash point	Not relevant
Evaporation rate	Not relevant
Flammability (solid, gas)	Not relevant
Upper Explosive Limit	Not relevant
Lower Explosive Limit	Not relevant
Vapour pressure	Not relevant
Vapour density	Not relevant
Relative density	1.089
Partition coefficient (n-octanol/water)	Not relevant
Viscosity	Not determined
Solubility	Soluble in water

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Skin corrosion/irritation	May cause irritation to skin. Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
---------------------------	---

## 140169 Primaprint RA38 Developer Replenisher Part A T/M 2x50L

Revision 3

Revision date 2018-07-25

## 11.1. Information on toxicological effects

Repeated or prolonged exposure	May cause allergic reactions in susceptible people. May cause severe irritation to eyes and skin.
--------------------------------	---

## SECTION 12: Ecological information

## 12.1. Toxicity

	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
--	---

## SECTION 13: Disposal considerations

## General information

	Dispose of in compliance with all local and national regulations.
--	---

## Disposal methods

	Do not empty into drains; dispose of this material and its container in a safe way. Do NOT mix with any other product. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
--	---

## SECTION 14: Transport information

## 14.1. UN number

	The product is not classified as dangerous for carriage.
--	--

## 14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.
--	--

## 14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.
--	--

## 14.4. Packing group

	The product is not classified as dangerous for carriage.
--	--

## 14.5. Environmental hazards

	The product is not classified as dangerous for carriage.
--	--

## 14.6. Special precautions for user

	The product is not classified as dangerous for carriage.
--	--

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	The product is not classified as dangerous for carriage.
--	--

## Further information

	Limited quantity.
--	-------------------

## SECTION 15: Regulatory information

## Further information

	No Significant Hazard.
--	------------------------

## SECTION 16: Other information

## Other information

Revision	This document differs from the previous version in the following areas:
----------	---

	14 - ADR/RID. 14 - IMDG. 14 - IATA.
--	---

Text of risk phrases in Section 3	R10 - Flammable R20/21 - Harmful by inhalation and in contact with skin. R22 - Harmful if swallowed. R36/37/38 - Irritating to eyes, respiratory system and skin. R53 - May cause long-term adverse effects in the aquatic environment.
-----------------------------------	---

Text of Hazard Statements in Section 3	Acute Tox. 4: H302 - Harmful if swallowed. Flam. Liq. 3: H226 - Flammable liquid and vapour.
--	---

## 140169 Primaprint RA38 Developer Replenisher Part A T/M 2x50L

Revision 3

Revision date 2018-07-25

**Other information**

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Acute Tox. 4: H312 - Harmful in contact with skin.  
Acute Tox. 4: H332 - Harmful if inhaled.

**Further information**

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.