

# SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

## 140113 CP-1 RA-RT Developer Replenisher 20L Drum

Revision 1  
Revision date 2022-10-07

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** 140113 CP-1 RA-RT Developer Replenisher 20L Drum

#### 1.3. Details of the supplier of the safety data sheet

**Company** Champion Photochemistry Sdn Bhd  
**Address** Lot 28-B Mukim Batu Industrial Area  
6 1/2 Miles Jalan Kepong  
52000 Kuala Lumpur  
MALAYSIA  
**Web** www.championphotochemistry.com  
**Telephone** +603-6257 2600  
**Fax** +603-6257 2622

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**2.1.1. Classification - 1999/45/EC** C; R35 Xn; R22-40 Xi; R43 N; R51/53  
Symbols: Xn: Harmful.

**Main hazards** Harmful if swallowed. Causes severe burns. Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**2.1.2. Classification - EC 1272/2008** Acute Tox. 4: H302; Skin Corr. 1A: H314; Skin Sens. 1: H317; Aquatic Chronic 2: H411;

#### 2.2. Label elements

##### Hazard pictograms



##### Signal Word

Danger

##### Hazard Statement

Acute Tox. 4: H302 - Harmful if swallowed.  
Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

##### Precautionary Statement: Prevention

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 - Wash thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

##### Precautionary Statement: Response

P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ if you feel unwell.  
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P302+P352 - IF ON SKIN: Wash with plenty of water/ .

## 140113 CP-1 RA-RT Developer Replenisher 20L Drum

Revision 1  
Revision date 2022-10-07

## 2.2. Label elements

<b>Precautionary Statement:</b> <b>Storage</b> <b>Precautionary Statement:</b> <b>Disposal</b>	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 -Immediately call a POISON CENTER/doctor/ . P321 - Specific treatment (see on this label). P330 - Rinse mouth. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P363 - Wash contaminated clothing before reuse. P391 - Collect spillage.
	P405 - Store locked up.
	P501 - Dispose of contents/container to hazardous or special waste collection point.

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

## 67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
DI Water		7732-18-5			20 - 30%		
Monoethylene glycol	603-027-00-1	107-21-1	203-473-3		20 - 30%	Xn; R22	
Polyethylene Glycol 400		25322-68-3	500-038-2		10 - 20%		
Potassium Carbonate		584-08-7	209-529-3		5 - 10%	Xi; R36/37/38	
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5		5 - 10%	C; R35	
Pentasodium DTPA Solution 42%		140-01-2	205-391-3		3 - 5%	C; R35 Xn; R22-40	
Diethylhydroxylamine 85% w/w		3710-84-7	223-055-4		1 - 3%	Xn; R20/21 Xi; R36/37/38 R10-53	
4-(N-Ethyl-N-2-methanesulphonylami noethyl)-2-methylphenylenediamine sesquisulphate monohydrate	612-134-00-2	25646-71-3	247-161-5		1 - 3%	Xn; R22 R43 N; R50/53	

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
DI Water		7732-18-5			20 - 30%		
Monoethylene glycol	603-027-00-1	107-21-1	203-473-3		20 - 30%	Acute Tox. 4: H302;	
Polyethylene Glycol 400		25322-68-3	500-038-2		10 - 20%		
Potassium Carbonate		584-08-7	209-529-3		5 - 10%	Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335;	
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5		5 - 10%	Skin Corr. 1A: H314;	
Pentasodium DTPA Solution 42%		140-01-2	205-391-3		3 - 5%	Met. Corr. 1: H290; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332; Repr. 2: H361d; STOT RE 2: H373;	
Diethylhydroxylamine 85% w/w		3710-84-7	223-055-4		1 - 3%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; Acute Tox. 4: H312; Acute Tox. 4: H332;	
4-(N-Ethyl-N-2-methanesulphonylami noethyl)-2-methylphenylenediamine sesquisulphate monohydrate	612-134-00-2	25646-71-3	247-161-5		1 - 3%	Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;	

## SECTION 4: First aid measures

## 140113 CP-1 RA-RT Developer Replenisher 20L Drum

Revision 1  
Revision date 2022-10-07

## 4.1. Description of first aid measures

Inhalation	Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Causes burns. Causes severe inflammation and may damage the cornea. Seek medical attention. Irritating to eyes.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion causes burns to the respiratory tract. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

	Not applicable. This product is not flammable.
--	--

## 5.2. Special hazards arising from the substance or mixture

	Corrosive. Burning produces irritating, toxic and obnoxious fumes.
--	--

## 5.3. Advice for firefighters

	Protective equipment. Wear suitable respiratory equipment when necessary. In case of fire and/or explosion do not breathe fumes.
--	--

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.
--	---

## 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

## 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.
--	--

## 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a dry, well ventilated area. Keep containers tightly closed.
--	--

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## 8.1.1. Exposure Limit Values

## 140113 CP-1 RA-RT Developer Replenisher 20L Drum


Revision 1

Revision date 2022-10-07

## 8.1.1. Exposure Limit Values

Monoethylene glycol	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: - WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: 40 WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: - WEL 8-hr limit mg/m3: 52 WEL 15 min limit mg/m3: 104 WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
Polyethylene Glycol 400	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: 10mg/m3 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
Potassium Carbonate	WEL 8-hr limit ppm: 370 mg/m3 WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
Sodium hydroxide	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: 2 WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -

## 8.2. Exposure controls

	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Not required under normal conditions of use.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

## 140113 CP-1 RA-RT Developer Replenisher 20L Drum

Revision 1  
Revision date 2022-10-07

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Orange
Odour	Slight
Odour threshold	Not relevant
pH	12.5
Melting point	Not relevant
Initial boiling point	100 °C
Flash point	Not relevant
Evaporation rate	Not relevant
Flammability (solid, gas)	Not relevant
Upper Explosive Limit	Not relevant
Lower Explosive Limit	Not relevant
Vapour pressure	2300 Pa
Vapour density	Not relevant
Partition coefficient (n-octanol/water)	Not relevant
Autolgnition temperature	Not relevant
Decomposition temperature	No data available
Viscosity	Not determined
Solubility	Soluble in water

## 9.2. Other information

Specific gravity	1.2 g/cm <sup>3</sup>
------------------	-----------------------

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

	No dangerous reaction known.
--	------------------------------

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## 10.3. Possibility of hazardous reactions

	No dangerous reaction known.
--	------------------------------

## 10.4. Conditions to avoid

	See "Fire Fighting Measures".
--	-------------------------------

## 10.5. Incompatible materials

	No relevant information available.
--	------------------------------------

## 10.6. Hazardous decomposition products

	No dangerous decomposition products known.
--	--

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Skin corrosion/irritation	May cause irritation to skin. Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Repeated or prolonged exposure	May cause allergic reactions in susceptible people. May cause severe irritation to eyes and skin.

## 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

## 12.1. Toxicity

	No data available
--	-------------------

## 140113 CP-1 RA-RT Developer Replenisher 20L Drum

Revision 1  
Revision date 2022-10-07

## 12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 12.2. Persistence and degradability

No data is available on this product.

## 12.3. Bioaccumulative potential

No data is available on this product.

## Partition coefficient

Pentasodium DTPA Solution <0  
42%

## 12.4. Mobility in soil

No data is available on this product.

## 12.5. Results of PBT and vPvB assessment

Not applicable.

## 12.6. Other adverse effects

No other relevant information available.

## SECTION 13: Disposal considerations

## General information

Dispose of in compliance with all local and national regulations.

## Disposal methods

Do not empty into drains; dispose of this material and its container in a safe way. Do NOT mix with any other product. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

## SECTION 14: Transport information

## 14.1. UN number

The product is not classified as dangerous for carriage.

## 14.2. UN proper shipping name

The product is not classified as dangerous for carriage.

## 14.3. Transport hazard class(es)

The product is not classified as dangerous for carriage.

## 14.4. Packing group

The product is not classified as dangerous for carriage.

## 14.5. Environmental hazards

The product is not classified as dangerous for carriage.

## 14.6. Special precautions for user

The product is not classified as dangerous for carriage.

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The product is not classified as dangerous for carriage.

## SECTION 15: Regulatory information

## Further information

Information contained in the MSDS is to our best present knowledge correct and complete and is given in good faith but without warranty.

## SECTION 16: Other information

## Other information

## 140113 CP-1 RA-RT Developer Replenisher 20L Drum

Revision 1  
Revision date 2022-10-07

## Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <p>2 - 2.1.2. Classification - EC 1272/2008.</p> <p>2 - Precautionary Statement: Prevention.</p> <p>2 - Precautionary Statement: Response.</p> <p>12 - 12.1. Toxicity.</p>
Text of risk phrases in Section 3	<p>R10 - Flammable</p> <p>R20/21 - Harmful by inhalation and in contact with skin.</p> <p>R22 - Harmful if swallowed.</p> <p>R35 - Causes severe burns.</p> <p>R36/37/38 - Irritating to eyes, respiratory system and skin.</p> <p>R40 - Limited evidence of a carcinogenic effect.</p> <p>R43 - May cause sensitisation by skin contact.</p> <p>R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R53 - May cause long-term adverse effects in the aquatic environment.</p>
Text of Hazard Statements in Section 3	<p>Acute Tox. 4: H302 - Harmful if swallowed.</p> <p>Skin Irrit. 2: H315 - Causes skin irritation.</p> <p>Eye Irrit. 2: H319 - Causes serious eye irritation.</p> <p>STOT SE 3: H335 - May cause respiratory irritation.</p> <p>Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.</p> <p>Met. Corr. 1: H290 - May be corrosive to metals.</p> <p>Acute Tox. 4: H332 - Harmful if inhaled.</p> <p>Repr. 2: H361d - Suspected of damaging the unborn child.</p> <p>STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .</p> <p>Flam. Liq. 3: H226 - Flammable liquid and vapour.</p> <p>Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.</p> <p>Acute Tox. 4: H312 - Harmful in contact with skin.</p> <p>Skin Sens. 1: H317 - May cause an allergic skin reaction.</p> <p>Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.</p>

## Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---